SOLID SHINE Series



	PT-RQ35K	30,500 lm 4K 32,000 lm (Center)	K	Gco.Pro
	PT-RZ34K	30,500 lm WUXGA 32,000 lm (Center)	4K	Geo.Pro

PT-RQ25K	20,000 lm 4K ²	1 K	E:B Geo.Pro
PT-RZ24K	21,000 lm (Center) 20,000 lm WUXGA	△K	Gco!Pro

PI-KQ ION	16,000 iiii	41	PROFESSIONAL	1111	Coo Des
	16,800 lm (Center)				OCUMPIO
рт- RZ17К	16,000 lm	WUXGA	ACCEPTS AK INSTALL		Geo.Pro

PT-RZ14K ³	14,000 lm WUXGA
-----------------------	-----------------




	PT-REQ15/L	15,000 lm	4K	# PREFFESS CHAN	△ K	Geolfro
-	PT-REQ12/L	12,000 lm 12,400 lm (Center)	4K	PROFESS CHAL	△K	Goodfro 🌑
	PT-REQ10/L	10,000 lm 10,300 lm (Center)	4K	PROFESS CHAL	4K	Gco.Pro
	PT-REQ80/L	8,000 lm 8,200 lm (Center)	4K	4	4K	Geo.Pro

*	PT- REZ15 /L ⁺	15,000 lm WUXGA	ACCEPTS AK		Geo.Pro
•	PT-REZ12/L ⁺	12,000 lm WUXGA 12,400 lm (Center)	ACCEPTS K	ak.	Geo.Pro
	PT-REZ10/L ⁺		ACCEPTS AK INVAL	ДK	Geo, Pro
	PT-REZ80/L ⁺	8,000 lm WUXGA 8,200 lm (Center)	ACCEPTS AK		Geo.Pro

	PT- RZ790 /L	7,000 lm WUXGA 7,200 lm (Center)	K	Geo.Pi
	PT- RZ690 /L	6,000 lm WUXGA 6,200 lm (Center)	AK	Geo.Pi





*	PT-MZ17KL	16,500 lm WUXGA	AK AK	Geo.Pro
	PT-MZ14KL	14,000 lm WUXGA	AK AK	Geo.Pro
	PT-MZ11KL	11,000 lm WUXGA	4K	Geo,Pro
*	PT-MZ882	8,200 lm WUXGA	-4K	

WUXGA

PT-MZ20KL 20,000 lm

			ESSVAL DELL	'Geo.Pr
	PT-MZ782	7,500 lm WUXGA		
(5)	PT- MZ682	6,500 lm WUXGA	AK	Geo.Pr

PT-LMZ460 4,600 lm



WUXGA









ET-SBFMP10 SDM type

- 1: Resolution 4096 x 2160 Pixels.
- 2: Resolution 3840 x 2400 Pixels (Quad Pixel Drive: ON).
- 3: Available in Japan, US and Canada
- 4: The availability varies depending on the country.
- 5: With Smooth Pixel Drive ON.
- 6: HDMI/DIGITAL LINK input only.
- 7: Resolution 3840 x 2160 Pixels (With Quad Pixel Drive).
- 8: HDMI input only. Supports signals up to 4K/30p.
- 9: HDMI/DIGITAL LINK input only. Supports signals up to 4K/30p.
- 10: To operate wireless projection, the optional Wireless Module AJ-WM50 is required.
- 11: To operate wireless projection, the optional Wireless Module ET-WML100 (Stock limited)/AJ-WM50 is required.
- * : Available in black/white cabinet.
- $\boldsymbol{\mathcal{E}}$: The projector is able to emulate the same control commands of most previous Panasonic projectors when it is replacing.
- +: Model is available in a TAA Compliant version

Note: [/L] Lens-less model. The specifications are subject to change without notice.



For more information about Panasonic Connect Projectors, please visit: https://na.panasonic.com/us/audio-video-solutions/projectors

High Brightness

NEW





*Actual Resolution: 3840 x 2160p

• DisplayPort (Ver. 1.2)



TH-43SQ2HW 700cd/m²





*Actual Resolution: 3840 x 2160p

• DisplayPort (Ver. 1.2)

Android OS







*Actual Resolution: 3840 x 2160p

тн- 86EQ2W	500cd/m ²	18h Operation	USB Media Player	Po <u>rtr</u> ait
тн- 75EQ2W	500cd/m ²	218h Operation	USB Media Player	Po <u>rtr</u> ait
тн- 65EQ2W	500cd/m ²	18h Operation	USB Media Player	Po <u>rtr</u> ait
тн- 55EQ2W	500cd/m ²	18h Operation	USB Media Player	Po <u>rtr</u> ait
тн- 50EQ2W	500cd/m ²	18h Operation	USB Media Player	Po <u>rtr</u> ait
тн- 43EQ2W	500cd/m ²	18h Operation	USB Media Player	Po <u>rtr</u> ait





*Actual Resolution: 3840 x 2160p

Android OS



Pitch for wall hanging is VESA compliant

NOTE: The availability varies depending on model. Market release schedules vary depending on the region. The specifications are subject to change without notice





Entry



PressIT360

TY-CSP1

• 360 degree Camera Speakerphone



